

| No. | Time     | Source         | Destination     | Protocol | Info                       |
|-----|----------|----------------|-----------------|----------|----------------------------|
| 9   | 4.723370 | 212.147.17.233 | 193.134.216.213 | SIP      | Request: REGISTER sip:spad |

Frame 9 (393 bytes on wire, 393 bytes captured)  
Ethernet II, Src: 00:d0:b7:8e:c3:8a, Dst: 00:0d:61:92:3d:1b  
Internet Protocol, Src Addr: 212.147.17.233 (212.147.17.233), Dst Addr: 193.134.216.213 (193.134.216.213)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol

Request-Line: REGISTER sip:spadatel.org SIP/2.0  
Message Header  
Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060  
Contact: sip:0244202373@10.2.15.60:5060  
Max-Forwards: 70  
Expires: 1800  
Supported: timer  
Content-Length: 0

| No. | Time     | Source          | Destination    | Protocol | Info                     |
|-----|----------|-----------------|----------------|----------|--------------------------|
| 10  | 4.725164 | 193.134.216.213 | 212.147.17.233 | SIP      | Status: 401 Unauthorized |

Frame 10 (688 bytes on wire, 688 bytes captured)  
Ethernet II, Src: 00:0d:61:92:3d:1b, Dst: 00:d0:b7:8e:c3:8a  
Internet Protocol, Src Addr: 193.134.216.213 (193.134.216.213), Dst Addr: 212.147.17.233 (212.147.17.233)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol

Status-Line: SIP/2.0 401 Unauthorized  
Message Header  
Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>;tag=b27e1a1d33761e85846fc98f5f3a7e58.0bed  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060;rport=5060;received=212.147.17.233  
WWW-Authenticate: Digest realm="spadatel.org", nonce="419e227097841c9b45eef4ebd3a1c4a8a29f1"  
Server: Sip spadatel.org (0.8.14 (i386/linux))  
Content-Length: 0  
Warning: 392 193.134.216.213:5060 "Noisy feedback tells: pid=14155 req src ip=212.147.17.233"

| No. | Time     | Source         | Destination     | Protocol | Info                       |
|-----|----------|----------------|-----------------|----------|----------------------------|
| 11  | 5.325788 | 212.147.17.233 | 193.134.216.213 | SIP      | Request: REGISTER sip:spad |

Frame 11 (393 bytes on wire, 393 bytes captured)  
Ethernet II, Src: 00:d0:b7:8e:c3:8a, Dst: 00:0d:61:92:3d:1b  
Internet Protocol, Src Addr: 212.147.17.233 (212.147.17.233), Dst Addr: 193.134.216.213 (193.134.216.213)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol

Request-Line: REGISTER sip:spadatel.org SIP/2.0  
Message Header  
Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060  
Contact: sip:0244202373@10.2.15.60:5060  
Max-Forwards: 70  
Expires: 1800  
Supported: timer  
Content-Length: 0

| No. | Time     | Source          | Destination    | Protocol | Info                     |
|-----|----------|-----------------|----------------|----------|--------------------------|
| 12  | 5.326900 | 193.134.216.213 | 212.147.17.233 | SIP      | Status: 401 Unauthorized |

Frame 12 (688 bytes on wire, 688 bytes captured)

Ethernet II, Src: 00:0d:61:92:3d:1b, Dst: 00:d0:b7:8e:c3:8a  
Internet Protocol, Src Addr: 193.134.216.213 (193.134.216.213), Dst Addr: 212.147.17.233 (212.147.17.233)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol  
Status-Line: SIP/2.0 401 Unauthorized  
Message Header  
Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>;tag=b27e1a1d33761e85846fc98f5f3a7e58.0bed  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060;rport=5060;received=212.147.17.233  
WWW-Authenticate: Digest realm="spadatel.org", nonce="419e2271f9c2ece77e2d552d04fc1edd26169"  
Server: Sip spadatel.org (0.8.14 (i386/linux))  
Content-Length: 0  
Warning: 392 193.134.216.213:5060 "Noisy feedback tells: pid=14154 req src ip=212.147.17.233"

| No. | Time     | Source         | Destination     | Protocol | Info                               |
|-----|----------|----------------|-----------------|----------|------------------------------------|
| 19  | 6.331183 | 212.147.17.233 | 193.134.216.213 | SIP      | Request: REGISTER sip:spadatel.org |

Frame 19 (393 bytes on wire, 393 bytes captured)  
Ethernet II, Src: 00:d0:b7:8e:c3:8a, Dst: 00:0d:61:92:3d:1b  
Internet Protocol, Src Addr: 212.147.17.233 (212.147.17.233), Dst Addr: 193.134.216.213 (193.134.216.213)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol  
Request-Line: REGISTER sip:spadatel.org SIP/2.0  
Message Header  
Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060  
Contact: sip:0244202373@10.2.15.60:5060  
Max-Forwards: 70  
Expires: 1800  
Supported: timer  
Content-Length: 0

| No. | Time     | Source          | Destination    | Protocol | Info                     |
|-----|----------|-----------------|----------------|----------|--------------------------|
| 20  | 6.332501 | 193.134.216.213 | 212.147.17.233 | SIP      | Status: 401 Unauthorized |

Frame 20 (688 bytes on wire, 688 bytes captured)  
Ethernet II, Src: 00:0d:61:92:3d:1b, Dst: 00:d0:b7:8e:c3:8a  
Internet Protocol, Src Addr: 193.134.216.213 (193.134.216.213), Dst Addr: 212.147.17.233 (212.147.17.233)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol  
Status-Line: SIP/2.0 401 Unauthorized  
Message Header  
Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>;tag=b27e1a1d33761e85846fc98f5f3a7e58.0bed  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060;rport=5060;received=212.147.17.233  
WWW-Authenticate: Digest realm="spadatel.org", nonce="419e2272959d6afc0f6c6550f5dbaa7d5834e"  
Server: Sip spadatel.org (0.8.14 (i386/linux))  
Content-Length: 0  
Warning: 392 193.134.216.213:5060 "Noisy feedback tells: pid=14154 req src ip=212.147.17.233"

| No. | Time     | Source         | Destination     | Protocol | Info                               |
|-----|----------|----------------|-----------------|----------|------------------------------------|
| 21  | 8.335449 | 212.147.17.233 | 193.134.216.213 | SIP      | Request: REGISTER sip:spadatel.org |

Frame 21 (393 bytes on wire, 393 bytes captured)  
Ethernet II, Src: 00:d0:b7:8e:c3:8a, Dst: 00:0d:61:92:3d:1b  
Internet Protocol, Src Addr: 212.147.17.233 (212.147.17.233), Dst Addr: 193.134.216.213 (193.134.216.213)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol  
Request-Line: REGISTER sip:spadatel.org SIP/2.0

Message Header

Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060  
Contact: sip:0244202373@10.2.15.60:5060  
Max-Forwards: 70  
Expires: 1800  
Supported: timer  
Content-Length: 0

| No. | Time     | Source          | Destination    | Protocol | Info                     |
|-----|----------|-----------------|----------------|----------|--------------------------|
| 22  | 8.336795 | 193.134.216.213 | 212.147.17.233 | SIP      | Status: 401 Unauthorized |

Frame 22 (688 bytes on wire, 688 bytes captured)  
Ethernet II, Src: 00:0d:61:92:3d:1b, Dst: 00:d0:b7:8e:c3:8a  
Internet Protocol, Src Addr: 193.134.216.213 (193.134.216.213), Dst Addr: 212.147.17.233 (212.147.17.233)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol

Status-Line: SIP/2.0 401 Unauthorized

Message Header

Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>;tag=b27e1a1d33761e85846fc98f5f3a7e58.0bed  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060;rport=5060;received=212.147.17.233  
WWW-Authenticate: Digest realm="spadatel.org", nonce="419e22740bc09f5905a252e1eaf0193918e20"  
Server: Sip spadatel.org (0.8.14 (i386/linux))  
Content-Length: 0  
Warning: 392 193.134.216.213:5060 "Noisy feedback tells: pid=14155 req src ip=212.147.17.233"

| No. | Time      | Source         | Destination     | Protocol | Info                               |
|-----|-----------|----------------|-----------------|----------|------------------------------------|
| 23  | 12.345465 | 212.147.17.233 | 193.134.216.213 | SIP      | Request: REGISTER sip:spadatel.org |

Frame 23 (393 bytes on wire, 393 bytes captured)  
Ethernet II, Src: 00:d0:b7:8e:c3:8a, Dst: 00:0d:61:92:3d:1b  
Internet Protocol, Src Addr: 212.147.17.233 (212.147.17.233), Dst Addr: 193.134.216.213 (193.134.216.213)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol

Request-Line: REGISTER sip:spadatel.org SIP/2.0

Message Header

Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060  
Contact: sip:0244202373@10.2.15.60:5060  
Max-Forwards: 70  
Expires: 1800  
Supported: timer  
Content-Length: 0

| No. | Time      | Source          | Destination    | Protocol | Info                     |
|-----|-----------|-----------------|----------------|----------|--------------------------|
| 24  | 12.346612 | 193.134.216.213 | 212.147.17.233 | SIP      | Status: 401 Unauthorized |

Frame 24 (688 bytes on wire, 688 bytes captured)  
Ethernet II, Src: 00:0d:61:92:3d:1b, Dst: 00:d0:b7:8e:c3:8a  
Internet Protocol, Src Addr: 193.134.216.213 (193.134.216.213), Dst Addr: 212.147.17.233 (212.147.17.233)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol

Status-Line: SIP/2.0 401 Unauthorized

Message Header

Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>;tag=b27e1a1d33761e85846fc98f5f3a7e58.0bed

CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060;rport=5060;received=212.147.17.233  
WWW-Authenticate: Digest realm="spadatel.org", nonce="419e227890db9783beaf0080b9036215e2af4"  
Server: Sip spadatel.org (0.8.14 (i386/linux))  
Content-Length: 0  
Warning: 392 193.134.216.213:5060 "Noisy feedback tells: pid=14154 req src ip=212.147.17.233"

| No. | Time      | Source         | Destination     | Protocol | Info                               |
|-----|-----------|----------------|-----------------|----------|------------------------------------|
| 34  | 20.380542 | 212.147.17.233 | 193.134.216.213 | SIP      | Request: REGISTER sip:spadatel.org |

Frame 34 (393 bytes on wire, 393 bytes captured)  
Ethernet II, Src: 00:d0:b7:8e:c3:8a, Dst: 00:0d:61:92:3d:1b  
Internet Protocol, Src Addr: 212.147.17.233 (212.147.17.233), Dst Addr: 193.134.216.213 (193.134.216.213)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol

Request-Line: REGISTER sip:spadatel.org SIP/2.0

Message Header

Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060  
Contact: sip:0244202373@10.2.15.60:5060  
Max-Forwards: 70  
Expires: 1800  
Supported: timer  
Content-Length: 0

| No. | Time      | Source          | Destination    | Protocol | Info                     |
|-----|-----------|-----------------|----------------|----------|--------------------------|
| 35  | 20.381742 | 193.134.216.213 | 212.147.17.233 | SIP      | Status: 401 Unauthorized |

Frame 35 (688 bytes on wire, 688 bytes captured)  
Ethernet II, Src: 00:0d:61:92:3d:1b, Dst: 00:d0:b7:8e:c3:8a  
Internet Protocol, Src Addr: 193.134.216.213 (193.134.216.213), Dst Addr: 212.147.17.233 (212.147.17.233)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol

Status-Line: SIP/2.0 401 Unauthorized

Message Header

Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>;tag=b27e1a1d33761e85846fc98f5f3a7e58.0bed  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060;rport=5060;received=212.147.17.233  
WWW-Authenticate: Digest realm="spadatel.org", nonce="419e22803198e00322f1e109c01680fb94610"  
Server: Sip spadatel.org (0.8.14 (i386/linux))  
Content-Length: 0  
Warning: 392 193.134.216.213:5060 "Noisy feedback tells: pid=14154 req src ip=212.147.17.233"

| No. | Time      | Source         | Destination     | Protocol | Info                               |
|-----|-----------|----------------|-----------------|----------|------------------------------------|
| 38  | 32.411423 | 212.147.17.233 | 193.134.216.213 | SIP      | Request: REGISTER sip:spadatel.org |

Frame 38 (393 bytes on wire, 393 bytes captured)  
Ethernet II, Src: 00:d0:b7:8e:c3:8a, Dst: 00:0d:61:92:3d:1b  
Internet Protocol, Src Addr: 212.147.17.233 (212.147.17.233), Dst Addr: 193.134.216.213 (193.134.216.213)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol

Request-Line: REGISTER sip:spadatel.org SIP/2.0

Message Header

Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060  
Contact: sip:0244202373@10.2.15.60:5060  
Max-Forwards: 70  
Expires: 1800

Supported: timer  
Content-Length: 0

| No. | Time      | Source          | Destination    | Protocol | Info                     |
|-----|-----------|-----------------|----------------|----------|--------------------------|
| 39  | 32.412619 | 193.134.216.213 | 212.147.17.233 | SIP      | Status: 401 Unauthorized |

Frame 39 (688 bytes on wire, 688 bytes captured)  
Ethernet II, Src: 00:0d:61:92:3d:1b, Dst: 00:d0:b7:8e:c3:8a  
Internet Protocol, Src Addr: 193.134.216.213 (193.134.216.213), Dst Addr: 212.147.17.233 (212.147.17.233)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol

Status-Line: SIP/2.0 401 Unauthorized

Message Header

Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>;tag=b27e1a1d33761e85846fc98f5f3a7e58.0bed  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060;rport=5060;received=212.147.17.233  
WWW-Authenticate: Digest realm="spadatel.org", nonce="419e228c81e019441fd23ea7541d72681a2d7"  
Server: Sip spadatel.org (0.8.14 (i386/linux))  
Content-Length: 0  
Warning: 392 193.134.216.213:5060 "Noisy feedback tells: pid=14154 req src ip=212.147.17.233"

| No. | Time      | Source         | Destination     | Protocol | Info                               |
|-----|-----------|----------------|-----------------|----------|------------------------------------|
| 49  | 48.452269 | 212.147.17.233 | 193.134.216.213 | SIP      | Request: REGISTER sip:spadatel.org |

Frame 49 (393 bytes on wire, 393 bytes captured)  
Ethernet II, Src: 00:d0:b7:8e:c3:8a, Dst: 00:0d:61:92:3d:1b  
Internet Protocol, Src Addr: 212.147.17.233 (212.147.17.233), Dst Addr: 193.134.216.213 (193.134.216.213)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol

Request-Line: REGISTER sip:spadatel.org SIP/2.0

Message Header

Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060  
Contact: sip:0244202373@10.2.15.60:5060  
Max-Forwards: 70  
Expires: 1800  
Supported: timer  
Content-Length: 0

| No. | Time      | Source          | Destination    | Protocol | Info                     |
|-----|-----------|-----------------|----------------|----------|--------------------------|
| 50  | 48.453423 | 193.134.216.213 | 212.147.17.233 | SIP      | Status: 401 Unauthorized |

Frame 50 (688 bytes on wire, 688 bytes captured)  
Ethernet II, Src: 00:0d:61:92:3d:1b, Dst: 00:d0:b7:8e:c3:8a  
Internet Protocol, Src Addr: 193.134.216.213 (193.134.216.213), Dst Addr: 212.147.17.233 (212.147.17.233)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol

Status-Line: SIP/2.0 401 Unauthorized

Message Header

Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>;tag=b27e1a1d33761e85846fc98f5f3a7e58.0bed  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060;rport=5060;received=212.147.17.233  
WWW-Authenticate: Digest realm="spadatel.org", nonce="419e229cf6a2f97407c796648dee0d677d5d4"  
Server: Sip spadatel.org (0.8.14 (i386/linux))  
Content-Length: 0  
Warning: 392 193.134.216.213:5060 "Noisy feedback tells: pid=14154 req src ip=212.147.17.233"

| No. | Time      | Source         | Destination     | Protocol | Info                               |
|-----|-----------|----------------|-----------------|----------|------------------------------------|
| 59  | 68.510417 | 212.147.17.233 | 193.134.216.213 | SIP      | Request: REGISTER sip:spadatel.org |

Frame 59 (393 bytes on wire, 393 bytes captured)  
Ethernet II, Src: 00:d0:b7:8e:c3:8a, Dst: 00:0d:61:92:3d:1b  
Internet Protocol, Src Addr: 212.147.17.233 (212.147.17.233), Dst Addr: 193.134.216.213 (193.134.216.213)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol

Request-Line: REGISTER sip:spadatel.org SIP/2.0

Message Header

Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060  
Contact: sip:0244202373@10.2.15.60:5060  
Max-Forwards: 70  
Expires: 1800  
Supported: timer  
Content-Length: 0

| No. | Time      | Source          | Destination    | Protocol | Info                     |
|-----|-----------|-----------------|----------------|----------|--------------------------|
| 60  | 68.511598 | 193.134.216.213 | 212.147.17.233 | SIP      | Status: 401 Unauthorized |

Frame 60 (688 bytes on wire, 688 bytes captured)  
Ethernet II, Src: 00:0d:61:92:3d:1b, Dst: 00:d0:b7:8e:c3:8a  
Internet Protocol, Src Addr: 193.134.216.213 (193.134.216.213), Dst Addr: 212.147.17.233 (212.147.17.233)  
User Datagram Protocol, Src Port: 5060 (5060), Dst Port: 5060 (5060)  
Session Initiation Protocol

Status-Line: SIP/2.0 401 Unauthorized

Message Header

Call-ID: 61a5-683a0-a022300@spadatel.org  
From: 0244202373<sip:0244202373@spadatel.org>;tag=35bb4-1fe3  
To: 0244202373<sip:0244202373@spadatel.org>;tag=b27e1a1d33761e85846fc98f5f3a7e58.0bed  
CSeq: 103 REGISTER  
Via: SIP/2.0/UDP 10.2.15.60:5060;rport=5060;received=212.147.17.233  
WWW-Authenticate: Digest realm="spadatel.org", nonce="419e22b08793ab44552612eea16e2135e3498"  
Server: Sip spadatel.org (0.8.14 (i386/linux))  
Content-Length: 0  
Warning: 392 193.134.216.213:5060 "Noisy feedback tells: pid=14154 req src ip=212.147.17.233"